



SIZE	25.4	38.1	50.8	63.5	76.1
ID	22.1	34.7	47.5	60.2	72.9
OD	25.4	38.1	50.8	63.5	76.1
AO	147	241	256	322	326
A1	15	26	25	32	32
A2	202	321	348	442	453
A3	15	26	25	32	32
B	35	80	80	80	80
C	55.6	80	92	120	128
E1	50.5	60	68.5	103.5	103.5
E2	58.5	68.5	68.5	103.5	103.5
t	1.65	1.65	1.65	1.65	1.65
L/ CLAMP	21.5	21.5	21.5	21.5	21.5
L/ SMS male	19	23	23	27	27
L/ IDF male	21.5	21.5	21.5	21.5	21.5
L/ RJT male	21.5	21.5	21.5	21.5	21.5

Materials:

- Product wetted steel parts:
AISI 316
- Other steel parts:
AISI 304
- Plug stem:
AISI 316 with chromium plated surface
- Product wetted seals:
EPDM
- Other seals:
NBR and EPDM
- Finish:
Semi bright

Technical data:

- Max product pressure:
1000kpa(10bar).
- Temperature range:
Full vacuum.
-10°C to +140°C
(EPDM).

SIZE	25.4	38.1	50.8	63.5	76.1
Id	22.1	34.7	47.5	60.2	72.9
øa	110	140	150	180	200
b	18	20	20	24	24
c	15	16	18	14	14
e	99	106	110	143	144
t	1.65	1.65	1.65	1.65	1.65

Type: L, T and L/L,
T/L, L/T, T/T

